

# LEACHING MACHINES

SERIES TA, TAH AND SL

FAST, CLEAN AND SECURE



Model  
TA-40



## INTENSIVE LEACHING BY DIPPING THE DOUGH

The sheets will not be dipped into the leach and stay completely dry, because of the baking paper. The operator will not get in touch with the leach. The dipping grid can be exchanged with one hand movement. Even the leach can be removed easily through the special drain cock. The 4 big casters make the machine mobile. Pastries can be put securely on the compact deposit table.

## LEACHING MACHINE FOR PULL-OFF DEVICE

The 4 big casters make the machine very mobile. In non-operating state the support sheets can be used as a compact storage table. The pull-off device is included in delivery.



## LEACHING MACHINE FOR PRETZEL PERFORATED PLATES

The machine has a special leaching pump and a leaching surge ledge available. The support sheets for the pretzel plates are folding upwards. The leach can be removed easily through the special drain cock.





## MODELS AVAILABLE

Leaching Machine  
Model TA-40 – TA-98

Model TAH

Leaching Machine for  
pull-off Device  
Model TA-160 – TA-200

Leaching Surge Machine  
Model SL

## STANDARD FEATURES

The stainless steel machines feature 4 big casters and a compact deposit table in non-operating state.

The model TAH features a heating.

The machines will be delivered with stainless steel pull-off device. All machines are deliverable with a heating.

The stainless steel machines with 4 big casters feature a special leaching pump and a leaching surge ledge, as well as swiveling support sheets for pretzel perforated plates.

## OPTIONAL FEATURES

Wooden trays with arbitrary line arrangement, dipping grids with arbitrary line arrangement, pretzel perforated plates.

Dipping grids with arbitrary line arrangement, pretzel breakover frame to charge the breakover boxes.

## TECHNICAL DATA:

	TA-40	TA-58	TA-78	TA-90	TA-98	TA-160	TA-180	TA-200	SL-05	SL-10	SL-20
Sheets (cm)	40x60	58x58	58x78	58x90	58x98	-	-	-	58x58	58x78	58x98
Width in rest position (mm)	550	740	740	740	740	1955	2155	2355	760	760	760
Width in working position (mm)	1080	1420	1420	1420	1420	1955	2155	2355	1660	2060	2460
Depth in rest position (mm)	685	665	865	985	1065	840	840	840	725	725	725
Depth in working position (mm)	685	665	865	985	1065	1525	1525	1525	725	725	725
Height (mm)	855	855	855	855	855	865	865	865	1500	1700	1900
Working Voltage (V) *	-	-	400	400	400	-	-	-	-	-	-
Rated Input (kW) *	-	-	4,5	6	7,5	-	-	-	-	-	-
Size of dipping grid (cm)	-	-	-	-	-	156x56	176x56	196x56	-	-	-
Charging with 2 wooden trays (cm)	-	-	-	-	-	58x78	58x90	58x98	-	-	-

\* Only machines with heating

Subject to change without notice